



ULTRACAB (INDIA) LIMITED
Survey No. 262, Behind Galaxy Bearings Ltd.
Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
Phone : 02827-253122 / 23, Fax : 02827-252725
Email : info@ultracab.in Web: www.ultracab.in
Customer Care Number: 1800 313 0323

LDC LP NO. 07/2020-21 Dt.15.12.2020

List Of Products Covered in LDC Price List	Page No.
Industrial Cables (House Wire FR/FRLS/HFFR)	1
Submersible Cables / Aluminium Service Cables / Aluminium Twin Flat Cables	2
Single Core & Multi Core Flexible Cables	3
Multicore Flat Elevator Cables / Solar Cables	4
BMS Cables / Welding Cables	5
Telephone Cables / CCTV Cables / Co - Axial Cables / Lan Cables	6
UL Approved Cables	7 - 8
Auto Cables	9



ULTRACAB (INDIA) LIMITED
 Survey No: 262, Behind Galaxy Bearings Ltd.
 Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
 Phone : 02827-253122 / 23, Fax : 02827-252725
 Email : info@ultracab.in Web: www.ultracab.in
 Customer Care Number: 1800 313 0323

REF NO-UIL/IC/LP-07/2020-21

DATE: 15.12.2020

FLAME RETARDANT (FR) INDUSTRIAL (MULTISTRAND) CABLE

ULTRACAB MAKE SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDENT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFIRMING TO IS - 694:2010

SIZE	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS)	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER MTR
0.75	24/0.20	7	945	28	1890	14	10.50
1.0	32/0.20	12	1280	20	2560	12	14.22
1.5	30/0.25	16	1865	16	3730	8	20.72
2.5	50/0.25	22	2940	10	5880	6	32.67
4.0	56/0.30	29	4305	8	8610	4	47.83
6.0	84/0.30	37	6430	6	12860	3	71.44

FLAME RETARDANT LOW SMOKE (FRLS) INDUSTRIAL (MULTISTRAND) CABLE

ULTRACAB MAKE SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFIRMING TO IS-694:2010.

SIZE	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS)	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER MTR
0.75	24/0.20	7	970	28	1940	14	10.78
1.0	32/0.20	12	1315	20	2630	12	14.61
1.5	30/0.25	16	1915	16	3830	8	21.28
2.5	50/0.25	22	3025	10	6050	6	33.61
4.0	56/0.30	29	4425	8	8850	4	49.17
6.0	84/0.30	37	6600	6	13200	3	73.33

HALOGEN FREE FLAME RETARDANT (HFFR) INDUSTRIAL (MULTISTRAND) CABLE

ULTRACAB MAKE SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - HALOGEN FREE FLAME RETARDANT (HFFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFIRMING TO IS-694:2010.

SIZE	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS)	RATE PER 90 MTR COIL	STANDARD PACKING FOR 90 MTR	RATE PER 180 MTR COIL	STANDARD PACKING FOR 180 MTR	RATE PER MTR
0.75	24/0.20	7	1015	28	2030	14	11.28
1.0	32/0.20	12	1375	20	2750	12	15.28
1.5	30/0.25	16	2005	16	4010	8	22.28
2.5	50/0.25	22	3160	10	6320	6	35.11
4.0	56/0.30	29	4360	8	8720	4	48.44
6.0	84/0.30	37	6910	6	13820	3	76.78

1) Prices:- The above rates are basic rate. GST Will be Charges Extra as applicable and subject to change as per Govt. rules

2) As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above in nominal. The size of the conductor is determined by its resistance . The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 With its related clauses and tables.

3) Alteration : This Price list is subjected to change without prior notice.



REF NO-UIL/LDC/LP-07/2020-21

DATE: 15.12.2020

ULTRACAB 3 CORE FLAT SUBMERSIBLE CABLES

Ultracab Make XLPE/PVC insulated and PVC Sheathed Industrial 3 Core & 4 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors With Voltage Grade up to 1100 Volts as per IS:694/2010

	Nominal Area of Conductor (sq.mm.)	Number/Nom.Dia of cables (No./dia mm)	3-Core Flat Cables Rate /100 Mtr (Rs)	4-Core Flat Cables Rate /100 Mtr (Rs)
Ultracab XLPE/PVC insulated and PVC Sheathed Industrial 3 Core & 4 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors With Voltage Grade up to 1100 Volts as per IS:694/2010	1.5	30/0.25	7646	9709
	2.5	50/0.25	12369	15707
	4	56/0.30	18155	23053
	6	84/0.30	26633	33820
	8	110/0.30	35501	45080
	10	140/0.30	45287	57507
	16	224/0.30	70623	89680
	25	350/0.30	111022	140980
	35	490/0.30	152418	193547
	50	700/0.30	228328	289940

ULTRACAB 3 & 4 CORE UNARMoured SERVICE CABLE

Ultracab Make Special XLPE insulated and PVC Sheathed 3 & 4 Core Aluminium Service Cable With Voltage Grade up to 1100 Volts as per IS:7098(PART-1)/1988

Nominal Area of Conductor (sq.mm.)	Number of Core	Rate per Mtr (Rs)	Number of Core	Rate per Mtr (Rs)
4 sq mm (Solid)	3	60	4	71
6 sq mm (Solid)	3	74	4	86
10 sq mm (Solid)	3	101	4	119
16 sq mm (STRANDED)	3	119	4	145
25 sq mm (STRANDED)	3	176	4	227
35 sq mm (STRANDED)	3	225	4	282
50 sq mm (STRANDED)	3	279	4	365

ULTRACAB 2 CORE ALUMINIUM TWIN FLAT CABLES

Ultracab Make Special PVC insulated and PVC Sheathed 2 Core Aluminium Twin Flat Service Cable With Voltage Grade up to 1100 Volts as per IS:694/2010

	Nominal Area of Conductor (sq.mm.)	Number of Core	Rate per Mtr (Rs)
Ultracab Make Special PVC insulated and PVC Sheathed 2 Core Aluminium Twin Flat Service Cable With Voltage Grade up to 1100 Volts as per IS:694/2010	2.5	2	24
	4	2	30
	6	2	42
	10	2	62

Notes:-

- Prices:- The above rates are basic rate. GST Will be Charges Extra as applicable and subject to change as per Govt. rules
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance . The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 with its related clauses and tables.
- Packing : a) 1.5 & 2.5 Sqmm Flat Submersible cable are supplied in 500 Mtr Coil Packing or 1000 Mtr Wooden Drum Packing b) 4.0 sq.mm. & above Flat Submersible cable are supplied in 500 Or 1000 Mtr Wooden Drum. C) Alu Unarm Cable are supplied in 500/1000 Mtr Wooden Drum Packing. d) Alu Twin Service Cables are supplied in 100 Mtr Coil Packing.
- Alteration : This Pricelist is subjected to change without prior notice.





ULTRACAB (INDIA) LIMITED
 Survey No. 262, Behind Galaxy Bearings Ltd.
 Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
 Phone : 02827-253122 / 23, Fax : 02827-252725
 Email : info@ultracab.in Web: www.ultracab.in
 Customer Care Number: 1800 313 0323

REF NO-UIL/LDC/LP-07/2020-21

DATE : 15.12.2020

ULTRACAB INDUSTRIAL FLEXIBLE CABLES

Ultracab PVC Insulated Unsheathed Bright Annealed Bare Copper Conductor Single Core Industrial Cable for Voltage Grade Upto 1100 Volts as per IS:694:2010

(Rate in Rs. Per 100 Mtrs)

Nominal Area of Conductor (sq.mm.)	Number/Nom. Dia of cables (No./dia mm)	Current Carrying Capacity (Amps)	Single core Packing	Single Core (Rate/100 Mtrs)	Nominal Area of Conductor (sq.mm.)	Number/Nom. Dia of cables (No./dia mm)	Current Carrying Capacity (Amps)	Single Core (Rate/100 Mtrs)
0.5	16/0.20	4	24	835	35	495/0.30	110	47690
0.75	24/0.20	7	24	1050	50	703/0.30	145	67450
1	32/0.20	12	20	1422	70	356/0.30	215	94905
1.5	30/0.25	16	16	2072	95	484/0.50	260	129295
2.5	50/0.25	22	12	3267	120	608/0.50	305	168720
4	56/0.30	29	8	4783	150	750/0.50	355	210520
6	84/0.30	37	4	7144	185	925/0.50	415	260110
10	140/0.30	51	1	13300	240	1210/0.50	500	335730
16	226/0.30	68	1	20832	300	1527/0.50	585	418665
25	356/0.30	86	1	34390	400	2036/0.50	695	557270

Ultracab PVC Insulated Unsheathed Bright Annealed Bare Copper Conductor PVC Insulated PVC Round Shethed Multi Core Industrial Cable for Voltage Grade Upto 1100 Volts as per IS:694:2010

Rate Per 100 Mtr

Nominal Area of Conductor (sq.mm.)	Number/Nom. Dia of cables (No./dia mm)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	8 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	2399	3211	4090	4912	5957	6603	7671	9500	11115	13110	14630	17100	21755
0.75	24/0.20	3187	4304	5539	6897	8360	9405	10830	13585	15675	18430	20900	24225	30305
1	32/0.20	3952	5434	6959	8883	10640	11875	13775	16910	19855	23370	26505	31350	39330
1.5	30/0.25	5363	7377	9690	12160	14630	16530	19190	23370	27550	32395	36765	43510	54720
2.5	50/0.25	8465	11970	15580	19665	23655	27170	32300	40375	47500	55575	63175	74100	93100
4	56/0.30	12730	18145	23655	31920	36765								
6	84/0.30	18145	26505	34675										
10	140/0.30	31540	45315	59565										
16	226/0.30	50350	71250	93860										
25	356/0.30	82650	119035	156940										
35	495/0.30	114570	165300	217360										
50	703/0.30		234460	309415										
70	356/0.50		326610	431965										

Notes :
 1) Prices:- The above rates are Basic rate. GST will be Charged extra as applicable and is subject to change as per Govt. rules.
 2) As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above in nonminal. The size the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. it may vary within the limits of IS:8130:1994 with its related clauses and tables.
 3)Packing : Ultracab Industrial Cable are supplied in 100m coils/500m Drums



**ULTRACAB (INDIA) LIMITED**

Survey No. 262, Behind Galaxy Bearings Ltd.
Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
Phone : 02827-253122 / 23, Fax : 02827-252725
Email : info@ultracab.in Web: www.ultracab.in
Customer Care Number: 1800 313 0323

REF NO-UIL/LDC/LP-07/2020-21

DATE: 15.12.2020

ULTRACAB MULTICORE ELEVATOR FLAT CABLES

Ultracab Make Bare Copper Conductor, PVC Insulated, TPR Sheathed Flat Cable with working Valtage Upto 1100 Volt

Nominal Area of Conductor (sq.mm.)	Number/No m. Dia of cables (No./dia mm)	Current Carrying Capacity (Amps)	(Rate per 100m - Rs)									
			4 Core	5 Core	6 Core	7 Core	8 Core	9 Core	10 Core	12 Core	14 Core	16 Core
0.5	16/0.20	4	6270	9025	10545	12350	14060	16150	18145	21375	25935	29165
0.75	24/0.20	7	7980	11780	14345	16340	18620	22040	24130	28690	33440	38760
1.0	32/0.20	12	9880	14915	17860	20615	23370	27455	29925	35720	42085	48545
1.5	30/0.25	16	13490	19380	22895	26410	30495	35055	39520	45790	54625	62225
2.5	50/0.25	22	21185	30685	36765	42845	49115	56905	62700	74765	87590	100700

SOLAR DC WIRES & CABLE**A) SOLAR WIRES & CABLE AS PER TUV/EN 50618**

Ultracab Make Flexible Tinned Copper Conductor Multistrand UV Stabilized Cross linked Insulated & Sheathed Zero Helogen Single Core Cable
Accordance to TUV 2pfg Standard./EN 50618

Size (sq.mm)	Rate Per 100m	Size (sq.mm)	Rate Per 100m
4.0	6840	35	53200
6.0	9690	50	76000
10	16055	70	106970
16	24795	95	140125
25	38380	120	177840

C) SOLAR WIRES & CABLE (TINNED COPPER) (ZHFR + ZHFR)

Ultracab Make Flexible Tinned Copper Conductor Multistrand ZHFR/ZHFR Insulation and UV Stabilized ZHFR Sheathed Single Core Cable

Size (sq.mm)	Rate Per 100m	Size (sq.mm)	Rate Per 100m
4.0	6080	35	52060
6.0	8740	50	74290
10	14915	70	115970
16	23180	95	157357
25	37525	120	198744

B) SOLAR WIRES & CABLE

Ultracab Make Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulation and UV Stabilized PVC Sheathed Single Core Cable

Size (sq.mm)	Rate Per 100m
4.0	5890
6.0	8645
10.0	14820
16.0	22895

NOTES:

1) Prices:- The above rates are basic rates. GST will be charged extra as applicable and is subject to change as per Govt. rules.

2) As per international practice which is also adopted by Bureau of Indian Standards, The diameter of the conductor shown above in nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 With its related clauses and tables.

3) Alteration : This Pricelist is subjected to change without prior notice.





ULTRACAB (INDIA) LIMITED
 Survey No. 262, Behind Galaxy Bearings Ltd.
 Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
 Phone : 02827-253122 / 23, Fax : 02827-252725
 Email : info@ultracab.in Web: www.ultracab.in
 Customer Care Number: 1800 313 0323

REF NO-UIL/LDC/LP-07/2020-21

DATE: 15.12.2020

ULTRACAB INDUSTRIAL SHIELDED CABLES (BUILDING MANAGEMENT SYSTEM CABLES - BMS)

Ultracab Make Flexible Bare Copper Conductor, PVC Insulated, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheathed Shielded Cable (Rates/100 Mtr)

Cores	0.50 sq.mm	0.75 sq.mm	1.0 sq.mm	1.50 sq.mm	2.50 sq.mm
2	4802	5700	6650	8615	13110
3	6047	7363	8788	11638	18288
4	7363	9144	11053	15200	23513
5	8669	10783	13181	18050	28500
6	10094	12706	15675	21375	34200
7	11115	14131	17575	24225	38475
10	15675	19713	24463	33963	54492
12	18050	23038	28975	40138	64296
14	20663	26600	33250	46075	74556
16	23275	30163	37525	52725	87438
19	27075	35150	43938	61750	101346
24	33725	44175	55575	77900	126882

ULTRACAB INDUSTRIAL WELDING CABLE

Ultracab Make Bare Copper Conductor, TPR Insulation Welding Cable

Nominal Area of Cond. (sq mm)	Current (AMP)	Conductor (Nos./mm.)	Rate/100 Mtrs
16	120	226/0.30	28975
25	160	356/0.30	43225
35	230	495/0.30	61038
50	400	703/0.30	86688
70	600	999/0.30	121125
95	700	1346/0.30	163400
120	1100	1699/0.30	202113

Notes:-

1) Prices:- The above rates are basic rate. GST will be charged extra as applicable and is subject to change as per Govt. rules

2) As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 With its related clauses and tables.

3) Alteration : This Pricelist is subjected to change Without prior notice.





ULTRACAB (INDIA) LIMITED
 Survey No. 262, Behind Galaxy Bearings Ltd.
 Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
 Phone : 02827-253122 / 23, Fax : 02827-252725
 Email : info@ultracab.in Web: www.ultracab.in
 Customer Care Number: 1800 313 0323

REF NO-UIL/LDC/LP-07/2020-21

DATE : 15.12.2020

ULTRACAB INDUSTRIAL TELEPHONE (SWITCHBOARD) CABLES

Ultracab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey OuterSheath generally conforming ITD Specification

No. of Pairs & Size	Rate per 100m coil		
	0.4 MM	0.5 MM	Master Packing (Nos.)
1 Pair	651	879	100 Mtr Coil
2 Pair	1150	1648	100 Mtr Coil
3 Pair	1667	2366	100 Mtr Coil
4 Pair	2100	3111	100 Mtr Coil
5 Pair	2779	3686	100 Mtr Coil
10 Pair	-	7363	100 Mtr Coil
20 Pair	-	15200	100 Mtr Coil
50 Pair	-	36860	100 Mtr Coil

ULTRACAB ARMoured TELEPHONE CABLES

No. of Pairs &	Rate / 100m (0.5 sqmm)	Packing
2 Pair	7900	Drums/Coils as required
5 Pair	12200	Drums/Coils as required
10 Pair	17900	Drums/Coils as required
20 Pair	23700	Drums/Coils as required

ULTRACAB CCTV (CAMERA) CABLES

CCTV (3+1)	100 MTR COIL	3396
CCTV (4+1)	100 MTR COIL	3829

ULTRACAB JELLY FLOODED COAXIAL CABLES

Ultracab Make Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Lacketed Coaxial Cables.

Size	100 Mtr Coil
RG - 6	2461
RG - 11	5358

ULTRACAB LAN (COMPUTER) CABLES

Ultracab Make 4 Pair Unshielded Twisted Pair (UTP) LAN (Computer) Cables

Size	PACKING	Unarmoured-Rate per 305 Mtrs
CAT 5 E	305 MTR	9500
CAT 6	305 MTR	10070

Notes:-

1) Prices:- The above rates are basic rate. GST will be charged extra as applicable and is subject to change as per Govt. rules

2) As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 With its related clauses and tables.

3) Alteration : This Pricelist is subjected to change Without prior notice.





ULTRACAB (INDIA) LIMITED
 Survey No. 262, Behind Galaxy Bearings Ltd.
 Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
 Phone : 02827-253122 / 23, Fax : 02827-252725
 Email : info@ultracab.in Web: www.ultracab.in
 Customer Care Number: 1800 313 0323

REF NO-UIL/LDC/LP-07/2020-21

DATE : 15.12.2020

ULTRACAB SINGLE CORE WIRES AS PER UL STANDARD

Ultracab Make PVC Insulated Unsheathed Single Core Industrial Wires with Bright Annealed Bare Copper Stranded Conductor as per UL Standard

UL STYLE SIZE (AWG)	(Rate per 100m -Rs)				
	UL 1007	UL 1015	UL 1032	UL 1569	UL 10012
24	741	773	790	784	806
22	1104	1154	1180	1170	1202
20	1482	1567	1598	1582	1629
18	2058	2141	2183	2166	2225
16	2965	3129	3194	3161	3260
14	-	4693	4776	4726	4874
10	-	11528	11758	11644	11989
8	-	18115	18478	18297	18841
6	-	27339	27882	27602	28442
4	-	43313	44203	43758	45093
2	-	69170	70552	69844	71969
1	-	85144	86842	-	88577
2/0	-	135046	137746	-	140498
3/0	-	172925	176385	-	179908
4/0	-	207861	218379	-	-
Temp. Rating	80' C	80'C, 90'C OR 105'C	90'C	80'C, 90'C OR 105'C	60'C, 80'C, 90'C OR 105'C
Voltage Rating	300 Volts	600 Volts	1000 Volts	300 Volts	1000 Volts

Notes:

1) Prices:- The above rates are basic rate. GST will be charged extra as applicable and is subject to change as per Govt. rules

2) As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 With its related clauses and tables.

3)Packing: Ultracab Industrial Cable are supplied in 100m coils/500m Drums

3) Alteration : This Pricelist is subjected to change Without prior notice.





ULTRACAB (INDIA) LIMITED
 Survey No. 262, Behind Galaxy Bearings Ltd.
 Shapar (Veraval)-360024, Dist.: Rajkot (GUJ) India
 Phone : 02827-253122 / 23, Fax : 02827-252725
 Email : info@ultracab.in Web: www.ultracab.in
 Customer Care Number: 1800 313 0323

REF NO-UIL/LDC/LP-07/2020-21

DATE : 15.12.2020

ULTRACAB MULTI CORE WIRES AS PER UL STANDARD

Ultracab Make PVC Insulated & PVC sheathed Multi Core Industrial Wires with Bright Annealed Bare Copper Stranded Conductor as per UL Standard

UL STYLE SIZE (AWG)		(Rate per 100 Mtr -Rs)						
		UL 2129	UL 2464	UL 2586	UL 2598	UL 2733	UL 20032	UL 20033
20	2 Core	4203	4119	4287	4035	4203	4119	4203
	3 Core	5624	5512	5737	5399	5624	5512	5624
	4 Core	7242	7097	7387	6952	7242	7097	7242
18	2 Core	6825	6689	6962	6552	6825	6689	6825
	3 Core	9313	9127	9499	8940	9313	9127	9313
	4 Core	11960	11720	12199	11481	11960	11720	11960
16	2 Core	9105	8922	9287	8740	9105	8922	9105
	3 Core	12719	12465	12974	12211	12719	12465	12719
	4 Core	16726	16392	17061	16057	16726	16392	16726
14	2 Core	14668	14374	14961	14081	14668	14374	14668
	3 Core	20537	20127	20948	19716	20537	20127	20537
	4 Core	26713	26179	27247	25645	26713	26179	26713
10	2 Core	31615	30982	32247	30350	31615	30982	31615
	3 Core	45829	44912	46746	43996	45829	44912	45829
	4 Core	59308	58122	60494	56936	59308	58122	59308
8	2 Core	54652	53559	55745	52466	54652	53559	54652
	3 Core	79159	77576	80742	75993	79159	77576	79159
	4 Core	102196	100152	104240	98108	102196	100152	102196
6	2 Core	89452	87663	91241	85874	89452	87663	89452
	3 Core	129399	126812	131987	124224	129399	126812	129399
	4 Core	170082	166680	173484	163279	170082	166680	170082
4	2 Core	170082	166680	173484	163279	170082	166680	170082
	3 Core	231351	226724	235978	222097	231351	226724	231351
	4 Core	304383	298295	310471	292208	304383	298295	304383
2	2 Core	232576	227924	237228	223273	232576	227924	232576
	3 Core	320803	314387	327219	307971	320803	314387	320803
	4 Core	420548	412137	428959	403726	420548	412137	420548
Temp. Rating	60°C, 80°C, 90°C OR 105°C	80° C	105°C	60° C	105° C	90° C	105° C	
Voltage Rating	600/1000	300 Volts	600/1000 V	300 Volts	600 Volts	600 Volts	600 Volts	

Notes:

1) Prices:- The above rates are basic rate. GST will be charged extra as applicable and is subject to change as per Govt. rules

2) As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 With its related clauses and tables.

3) Packing : Ultracab Industrial Cable are supplied in 100m coils/500m Drums

4) Alteration : This Pricelist is subjected to change Without prior notice.



SINGLE CORE AUTOMOTIVE CABLES PRICELIST

REF NO-UIL/LDC/LP-07/2020-21

DATE : 15.12.2020

ULTRACAB MAKE 1 CORE FLRY-A or FLRY-B AUTO CABLES

Ultracab Make Bare Copper Flexible Conductor, PVC Insulated Single Core Automotive FLRY-A Or FLRY-B Wire

Ultracab Make Bare Copper Flexible Conductor, PVC Insulated Single Core Automotive FLRY-A Or FLRY-B Wire	Nominal Area of Conductor (SQMM)	Rate per 100 Mtr (Rs)
		0.5
	0.75	1299
	1	1691
	1.5	2489
	2.5	4117
	4	6228
	6	9185
	10	16277
	16	25215
	25	39642

ULTRACAB MAKE SINGLE CORE TXL CABLES

ULTRACAB MAKE BARE COPPER FLEXIBLE CONDUCTOR, XLPE INSULATED TXL WIRE AS PER SAE J - 1128

ULTRACAB MAKE BARE COPPER FLEXIBLE CONDUCTOR, XLPE INSULATED TXL WIRE AS PER SAE J - 1128	Nominal Area of Conductor (AWG)	Rate per 100 Mtr (Rs)
		22
	20	1369
	18	1775
	16	2714
	14	4323
	12	6539
	10	9647

ULTRACAB MAKE SINGLE CORE GXL CABLES

ULTRACAB MAKE BARE COPPER FLEXIBLE CONDUCTOR, XLPE INSULATED GXL WIRE AS PER SAE J - 1128

ULTRACAB MAKE BARE COPPER FLEXIBLE CONDUCTOR, XLPE INSULATED GXL WIRE AS PER SAE J - 1128	Nominal Area of Conductor (AWG)	Rate per 100 Mtr (Rs)
		20
	18	1865
	16	2846
	14	4537
	12	6865
	10	10123
	8	17900

Notes:-

1) Prices:- The above rates are basic rate. GST will be charged extra as applicable and is subject to change as per Govt. rules

2) As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS :8130:1994 With its related clauses and tables.

3) Packing : 100 Mtr Shrink wrapped Coil Packing or 1000 Mtr Plastic / wooden Drum Packing

3) Alteration : This Pricelist is subjected to change Without prior notice.

